

TESTING CAMPAIGN ON THE ENERGETICAL AND ACOUSTICAL BEHAVIOUR OF A HEAT PUMP // PART1

IEA HPT Annex 51 “Acoustic Signatures of Heat Pumps”



Simon Braungardt, Thomas Gindre, Thore Oltersdorf,
Agostino Troll

Fraunhofer Institute for Solar Energy Systems ISE

Fraunhofer Institute for Building Physics IBP

The 25th International Congress of Refrigeration

Montreal, Quebec, Canada | August 24-30

www.ise.fraunhofer.de

AGENDA



- 1. Acoustic measurements: goals and suited devices
- 2. Deconstruction analysis: concept and experimental setup
- 3. Results

AGENDA

- 1. Acoustic measurements: goals and suited devices
- 2. Deconstruction analysis: concept and experimental setup
- 3. Results



1. Acoustic measurements: goals and suited devices

- Microphones in reverberation chamber → Sound pressure → Sound Power




1. Acoustic measurements: goals and suited devices

- Microphones in reverberation chamber → Sound pressure → Sound Power
- Comparison of spectra with accelerometers:
→ Identification of the contributions from the individual sound sources



1. Acoustic measurements: goals and suited devices



- Microphones in reverberation chamber → Sound pressure → Sound Power
- Comparison of spectra with accelerometers:
 - Identification of the contributions from the individual sound sources
- → **Assessment** of the overall noise emission



Source: avisolartech.com

1. Acoustic measurements: goals and suited devices

- Microphones in reverberation chamber → Sound pressure → Sound Power
- Comparison of spectra with accelerometers:
 - Identification of the contributions from the individual sound sources
- → **Assessment** of the overall noise emission
 - but no direct insight into transfer paths or structural stress.



Source: avisolartech.com

1. Acoustic measurements: goals and suited devices

The 3D-Laservibrometer allows measurements of:

- local triaxial vibration velocities (similarly to accelerometers)
- without object contact
- many points in a short time with phase reference
→ acquisition of vibrations over a whole surface.



1. Acoustic measurements: goals and suited devices

The 3D-Laservibrometer allows measurements of:

- local triaxial vibration velocities (similarly to accelerometers)
- without object contact
- many points in a short time with phase reference
→ acquisition of vibrations over a whole surface.
- Direct assessment of:
 - precise excitation spectrum for each source
 - transfer paths through the structure
 - structure load/weaknesses (in theory even structure strain)
- Also useful for **system design** and
control strategy **improvements**



AGENDA

- 1. Acoustic measurements: goals and suited devices
- 2. Deconstruction analysis: concept and experimental setup
- 3. Results

2. Deconstruction analysis: concept and experimental setup

- Thermic setup:
Climatic chamber +
cooling heat exchanger +
power monitoring.





2. Deconstruction analysis: concept and experimental setup

■ Thermic setup:

Climatic chamber +
cooling heat exchanger +
power monitoring.


■ Acoustic setup:

microphones +
accelerometers +
3D-laservibrometer




2. Deconstruction analysis: concept and experimental setup


- Measurements states
 - different states of dismantlement



1



2



3

2. Deconstruction analysis: concept and experimental setup

- Measurements states
 - different states of dismantlement
 - different operating conditions (+ transient states like defrosting)

Zustand	Feuchte	Leistung	kompositionszustai	Frostzustand	Gehäuse
A2/W35	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A-15/W35	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A-15/W45	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A-15/W55	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A-15/W65	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A-7/W35	Feuchtkugel -8°C	100%	Komplett	Frostfrei	Ohne Gehä
A7/W35	Feuchtkugel 6°C	100%	Komplett	Frostfrei	Ohne Gehä
A12/W55	Feuchtkugel 11°C	100%	Komplett	Frostfrei	Ohne Gehä
A2/W35		100%	Nur Verdichter	-	Ohne Gehä
A12/W55		100%	Nur Verdichter	-	Ohne Gehä
A12/W55			Nur Berieselung und	-	Ohne Gehä
A12/W55			Nur Berieselung	-	Ohne Gehä
A12/W55			Nur Ventilator	-	Ohne Gehä
A7/W35		100%	Nur Verdichter	-	Ohne Gehä
A-7/W35		100%	Nur Verdichter	-	Ohne Gehä
A-15/W35		100%	Komplett	-	Ohne Gehä
A-15/W45		100%	Komplett	-	Ohne Gehä
A-15/W35		100%	Nur Verdichter	-	Ohne Gehä
A2/W35	trocken	37%	Komplett	Frostfrei	Ohne Gehä
A2/W35	trocken	100%	Komplett (vor Abta	Frostfrei	Ohne Gehä
A2/W35	trocken	100%	Komplett (nach Abt	Frostfrei	Ohne Gehä
A2/W55	trocken	100%	Komplett	Frostfrei	Ohne Gehä
A2/W35	trocken	20%	Komplett	Frostfrei	Mit Gehä
A2/W35	trocken	20%	Nur Ventilator	Frostfrei	Mit Gehä
A2/W35	trocken	37%	Komplett	Frostfrei	Mit Gehä